

型号编码: ISM2008D-<N1>T-<N2><F><L><W>-FC/SC-24/48w

型号命名规则	型号编码描述	ISM2008D	N1	N2	F	L	W	FC/SC	24/48w
		子系列	电口数量	光口数量	光纤类型 M: 多模双纤 S: 单模双纤 B: 单模单纤	传输距离 20/40/60/80/120 KM (多模距离为 2KM, 默认省略)	发/收波长 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	接口类型 FC、SC可选	供电电压 24VDC (18~36VDC)/48VDC (36~72VDC) 可选
	示例					ISM2008D-6T-2M3-FC-24	ISM2008D-6T-2B2053-SC-24	ISM2008D-8T-24	
可选端口组合 (即<N1>T-<N2><F><L><W>-部分)					电口	6T	8T		
					光口数: 2	光口数: 0			
					2M3	-			
					2S203	-			
					2S205	-			
					2S403	-			
					2S405	-			
					2S603	-			
					2S605	-			
					2S803	-			
					2S805	-			
					2B2053	-			
					2B2035	-			
					2B4053	-			
					2B4035	-			
2B6053	-								
2B6035	-								
					光口				