

型号编码：ISM2009D-<N1>T-<N2><F><L><W>-FC/SC-24/48w

型号命名规则	型号编码描述	ISM2009D	N1	N2	N3	F	L	W	FC/SC	24/48w
		子系列	电口数量	第一种类型 光口数量 (简称：I 型光口数)	第二种类型 光口数量 (简称：II 型光口数)	光纤类型 M：多模双纤 S：单模双纤 B：单模单纤	传输距离 20/40/60/8 0/120 KM (多模距离 为2KM，默 认省略)	发/收波长 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	接口类型 FC、SC可 选	供电电压 24VDC (18~36VDC (36~72VDC) 可选
	示例									ISM2008D-6T-2M3-FC-24 ISM2008D-6T-2B2053-SC-24 ISM2009D-9T-24
			电口				6T			9T
							I型光口数：3 II型光口数：0			I型光口数：3 II型光口数：0
							3M3			2S203-M3
							3S203			2S205-M3
							3S205			2S403-M3
							3S403			2S405-M3
							3S405			2S603-M3
							3S603			2S605-M3
							3S605			2S803-M3
							3S803			2S805-M3
							3S805			2B2053-M3
							3B2053			2B2035-M3
							3B2035			2B4053-M3
							3B4053			2B4035-M3
							3B4035			2B6053-M3
							3B6053			2B6035-M3
							3B6035			-
			光口							
			可选端口组合 (即<N1>T-<N2><F><L><W>- <N3><F><L><W>部分)							