

型号编码：ISM3010D-<N1>T-2GSFP-<N2><F><L><W>-FC/SC-24/48w

型号命名规则	型号描述	ISM3010D	N1	GSFP	N2	N3	F	L	W	FC/SC	24/48w
		子系列	电口数量	千兆SFP口	第一种类型 光口数量 (简称：I型 光口数)	第二种类型 光口数量 (简称：II 型光口数)	光纤类型 M: 多模双纤 S: 单模双纤 B: 单模单纤	传输距离 20/40/60/80/120 KM (多模距离为2KM, 默认省略)	发/收波长 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	接口类型 FC、SC可选	供电电压 24VDC (18~36VDC) /48VDC (36~72VDC) 可选
示例		ISM3010D-6T-2GSFP-2M3-FC-24 ISM3010D-8T-2GSFP-24									
<p style="text-align: center;">可选端口组合 (即<N1>T-2GSFP-<N2><F><L><W>-<N3><F><L><W>部分)</p>	电口		6T				8T				
			光口数: 2				光口数: 0				
			2M3				-				
			2S203				-				
			2S205				-				
			2S403				-				
			2S405				-				
			2S603				-				
			2S605				-				
			2S803				-				
			2S805				-				
			2B2053				-				
			2B2035				-				
			2B4053				-				
			2B4035				-				
		2B6053				-					
		2B6035				-					
		光口									