

型号编码：ISM2005D-<N1>T-<N2><F><L><W>-FC/SC-24/48w

型号命名规则	型号编码描述	ISM2005D	N1	N2	F	L	W	FC/SC	24/48w
		子系列	电口数量	光口数量	光纤类型 M: 多模双纤 S: 单模双纤 B: 单模单纤	传输距离 20/40/60/80/120 KM (多模距离为2KM, 默认省略)	发/收波长 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	接口类型 FC、SC可选	供电电压 24VDC (18~36VDC) /48VDC (36~72VDC)) 可选
	示例					ISM2005D-3T-2M3-FC-24	ISM2005D-3T-2S203-SC-24	ISM2005D-5T-24	
					电口	3T	5T		
						光口数: 2	光口数: 0		
						2M3	-		
						2S203	-		
						2S205	-		
						2S403	-		
						2S405	-		
						2S603	-		
						2S605	-		
						2S803	-		
						2S805	-		
						2B2053	-		
						2B2035	-		
						2B4053	-		
						2B4035	-		
						2B6053	-		
						2B6035	-		
					光口				

可选端口组合
(即<N1>T-<N2><F><L><W>-部分)