

型号编码：ISM3028U-4GS -8T-<N1>T-<N2><F><L><W>-FC/SC-HV/HV-HV

型号命名规则	型号编码描述	ISM3028U	4GSFP	8T	N1	N2	F	L	W	FC/SC	HV/HV-HV
		子系列	四个千兆 SFP口	8个固定电口数	电口数	光口数	光纤类型 M: 多模双纤 S: 单模双纤 B: 单模单纤	传输距离 20/40/60/80/120 KM (多模距离为2KM, 默认省略)	发/收波长 3:Tx1310/Rx1310nm 5:Tx1550/Rx1550nm 53:Tx1550/Rx1310nm 35:Tx1310/Rx1550nm	接口类型 FC、SC可选	支持单电源/支持双冗余电源
	示例	ISM3028U-4GSFP-8T-8T-8T-HV ISM3028U-4GSFP-8T-8T-4T4S203SC-HV									
					电口		0T (省略)	2T	4T	6T	8T
							光口数: 8	光口数: 6	光口数: 4	光口数: 2	光口数: 0
							8M3	6M3	4M3	2M3	-
							8S203	6S203	4S203	2S203	-
							8S205	6S205	4S205	2S205	-
							8S403	6S403	4S403	2S403	-
							8S405	6S405	4S405	2S405	-
							8S603	6S603	4S603	2S603	-
							8S605	6S605	4S605	2S605	-
							8S803	6S803	4S803	2S803	-
							8S805	6S805	4S805	2S805	-
							8B2053	6B2053	4B2053	2B2053	-
							8B2035	6B2035	4B2035	2B2035	-
							8B4053	6B4053	4B4053	2B4053	-
							8B4035	6B4035	4B4035	2B4035	-
							8B6053	6B6053	4B6053	2B6053	-
							8B6035	6B6035	4B6035	2B6035	-
					光口						

可选端口组合
(即<N1>T-<N2><F><L><W>-<N3><F><L><W>部分)